



DOUBLE 2X6 WITH 2X4 ON EACH SIDE-FLOOR TO CEILING AT EACH FLOOR

ANCHOR LOCATIONS

DETAIL J SCALE 1 : 4

- Battery Powered: 24 VDC Control System
- Rated Load: 500 lbs
- Speed: 15 fpm
- Max. Travel: 21'-0"
- Winding Drum Drive with dual 1/4" aircraft cables
- Automatic up/down controls
- Key Lock on controls
- Emergency Stop Switch and Alarm
- Recessed LED Car Light
- Status LED
- Door Position switch on Sliding Car Door
- Slack Cable Safety Device
- Final Limit Switch

SECTION A-A SCALE 1 : 16

SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAYING HOME CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAYING HOME CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DIMENSIONS ARE IN INCHES		DRAWN	7/16/2019	
TOLERANCES:		CHECKED		TITLE:
FRACTIONAL: ±1/16		ENG APPR.		EZ6 90° FRONT/RIGHT ENTRY
ANGULAR: ±0.5°		MFG APPR.		SIZE DWG. NO. REV
ONE PLACE DECIMAL ±0.1		Q.A.		B TYP - EZ6-90R
TWO PLACE DECIMAL ±0.01		PROJECT:		SCALE: 1:96 WEIGHT: SHEET 1 OF 1
THREE PLACE DECIMAL ±0.005				
INTERPRET GEOMETRIC TOLERANCING PER:				
MATERIAL				
FINISH				
DO NOT SCALE DRAWING				